

**ALTEC GmbH**

Rudolf-Diesel-Straße 7
D-78224 Singen

Telefon: 0 77 31/87 11-0
Telefax: 0 77 31/87 11 11

ALTEC GmbH · Rudolf-Diesel-Straße 7 · D-78224 Singen

Internet: www.altec.de
E-Mail: info@altec.de

Technical Datasheet AOS 08101021

Type	AOS_300
Version	without curb
Type of connection/support	Lip 155
Length L	1995 mm
Total width	305 mm
External width dimension B	300 mm
Internal Width Dimension B	300 mm
Height of construction dim. H	60 mm
Weight/piece	11 kg
Max. capacity specified in daN per ramp:	
for vehicles with two axles with	
Axle load distribution 40% to 60%	
Capacity at axle distance 0,75 mtrs	395 daN(kp)
Capacity at axle distance 1,00 mtrs	450 daN(kp)
Capacity for one axle vehicle	285 daN(kp)
max. height difference at 30% HDmax	540 mm
min. height difference HDmin	310 mm
Running surface	perforated
including slip off safety device	yes
including steel pin safety device	yes
according to drawing	110.4070

Made in Germany

These ramps are not suitable for driving on
directly with steel tracked vehicles. Please put a
working part (wood) between ramp and steel track.